


FEATURES:

- Input: AC 100-240V~ 50/60Hz
- AC INLET: C8 or C6 or C14
- Power: 72-84W series
- Ovp, ocp, scp and Over load protection
- Ripple < 120mV
- Efficiency level: VI
- Dimension: 112.6*60.2*35mm
- Application: Consumer electronics, Telecom and office equipment



SAFETY:

SAFETY:	
Safety Standard	UL 62368, IEC 62368, EN 61558, IEC60601, IEC60335
Safety Approval	UL/cUL, CE, FCC, UKCA, PSE, CB, SAA, KC, TUV
EMC Standard	EMC EMISSION: EN55035 class B (CISPR32), EN61000-3-2,-3, EAC TP TC 020 EMC IMMUNITY: EN61000-4-2,3,4,5,6,8,11, EN55024; light industry level, criteria A, EAC TP TC 020
MTBF	50K hrs min. MIL-HDBK-217F (25°C)

MODEL LIST:

72W DESKTOP ADAPTERS SERIES

MODEL	INPUT VOLTAGE	POWER	OUTPUT VOLTAGE	OUTPUT CURRENT	INLET TYPE
SW-00090700-S10	100-240VAC	63W	9V	7.0A	C8, C6, C14
SW-00120600-S10	100-240VAC	72W	12V	6.0A	C8, C6, C14
SW-00150500-S10	100-240VAC	75W	15V	5.0A	C8, C6, C14
SW-00240300-S10	100-240VAC	72W	24V	3.0A	C8, C6, C14
SW-00480150-S10	100-240VAC	72W	48V	1.5A	C8, C6, C14

84W DESKTOP ADAPTERS SERIES

MODEL	INPUT VOLTAGE	POWER	OUTPUT VOLTAGE	OUTPUT CURRENT	INLET TYPE
SW-00090800-S10	100-240VAC	72W	9V	8.0A	C8, C6, C14
SW-00120700-S10	100-240VAC	84W	12V	7.0A	C8, C6, C14
SW-00150560-S10	100-240VAC	84W	15V	5.6A	C8, C6, C14
SW-00240350-S10	100-240VAC	84W	24V	3.5A	C8, C6, C14
SW-00480175-S10	100-240VAC	84W	48V	1.75A	C8, C6, C14

Mechanical Diagram:

